

STANDING RIGGING SCHEDULE.

WIRE.	KEY.	MAST DIAGRAM.	WIRE CIRC. WIRE DIA.		DETAILS.	
			1 x 19 STAINLESS STEEL.		TOP END	BOTTOM END
FORESTAY.	1.		3/4" Circ	6mm DIA.		
BACKSTAY.	2.		3/4" Circ	6mm DIA.		
MAIN CAP SHROUDS	3.		3/4" Circ	6mm DIA.		
FWD. LOWER SHROUDS	4.		5/8" Circ.	5mm DIA.		
AFT LOWER SHROUDS	5.		5/8" Circ	5mm DIA.	AS ABOVE.	
			ALL SWAGE TERMINALS & BOTTLESCREWS SUPPLIED BY HASSELFORDS.			

SEE ALSO DRG. No. 1. FOR FURTHER RIGGING DETAILS

GENERAL NOTES.

A. REFER FOR FURTHER INFORMATION ON RIGGING DETAILS TO DRAWING NUMBERS 1, & KEY PLAN,

"SAIL PLAN" & "DECK PLAN, DECK COLLAR & HEEL SUPPORT."

B. ABBREVIATIONS ON BOTH SCHEDULES :-

- (i) SN/SH = SNAP SHACKLE
- (ii) CH/P.T. = CHAINPLATE.
- (iii) SH. = SHACKLE OR SHEAVE.
- (iv) DBL. = DOUBLE BLOCK.
- (v) BK. = BECKET.
- (vi) M/Hd = MASTHEAD.
- (vii) B/SCREEN = BOTTLESCREW/TERMINAL (HASSELFORDS S/S)
- (viii) S/S = STAINLESS STEEL TO MARINE STANDARD EN 58J.

RUNNING RIGGING SCHEDULE.

DESCRIPTION.	DIAGRAM.	WIRE	ROPE	COLOUR CODE & DESCRIPTION	FURTHER PARTICULARS.
		SPEC. DIA.	CIRC. DIA.		
MAIN HALYARD (INTERNAL)		8x19 S/S	5mm 1/4" 10mm	WHITE	MAIN HALYARD WINCH LEWMAR 8 MOUNTED ON MAST WIRE & ROPE TAIL SH ON HALYARD END TO FIT MAINSAIL HEADBOARD
GENOA (INTERNAL)		6x19 S/S	5mm 1/4" 10mm	WHITE & BLUE FLECKED.	GENOA HALYARD WINCH LEWMAR 25 MOUNTED PORT SIDE AT AFT END OF COACHROOF SWB TO SUIT HEAD OF HEADSAILS WIRE WITH ROPE TAIL.
SPARE (INTERNAL)	AS ABOVE	6x19 S/S	5mm 1/4" 10mm	WHITE	"
" (INTERNAL)	AS ABOVE	6x19 S/S	5mm 1/4" 10mm	WHITE	"
SPINNAKER HALYARD (INTERNAL)			1" 8mm	WHITE	SPINNAKER HALYARD WINCH LEWMAR 8 MOUNTED ON STARBOARD SIDE AT AFT END OF COACHROOF WIRE WITH ROPE TAIL
MAINSHEET.		6x19 S/S	5mm 1/4" 10mm	WHITE	FIXED EYE & EYE STRAP SHACKLED TO BOOM END & LOWER DOUBLE BLOCK & BECKET LOWER BLOCK SHACKLED TO TRACK SUPER & FITTED WITH CAM CLEATS TO SERVE ADJUSTMENT LINES P/B.
GENOA SHEETS.			1/2" 12mm	WHITE	* SHACKLED TO CLEW OF SAIL
TOPPING LIFT (INTERNAL)		6x19 S/S	4mm 3/4" 6mm	WHITE	ROPE TAIL OF WIRE LIFT LEADING TO CLEAT AT STARBOARD AFT END OF COACHROOF SH TO EYE TO SUIT BOOM END FITTING CLEAT ON DECK
KICKING STRAP.		6x19 S/S	5mm 1" 8mm	WHITE	FIXED EYE & EYE STRAP SHACKLED TO BEWINDER & DOUBLE BLOCK DOUBLE BLOCK & BECKET SHACKLED TO MAST FITTING " " FITTED WITH CAM CLEAT ROPE TO SUIT.
SPINNAKER SHEET.			1/4" 10mm	RED	SNAP SHACKLED X2 TO SUIT SPINNAKER CLEWS.
" GUY.			1/4" 10mm	GOLD	SNAP SHACKLES X2 TO SUIT SPINNAKER CLEWS.
" TOPPING LIFT (INTERNAL)			1" 8mm	WHITE	INTERNAL MAST SHEAVES X2 FITTED TO MAST ABOVE SPREADERS 2 x 21/32" TO SUIT SPINNAKER BOOM END FITTING
" DOWNHAUL			1" 8mm	WHITE	SNAP SHACKLE TO SUIT UNDERSIDE OF BOOM END FITTING SINGLE BLOCK, EYE, & SHACKLE ROPE TO SUIT BLOCK SIZE
" POLE HEEL FITTING ARRANGEMENT.					TWIN SLIDING CUPS FITTED TO LEWMAR FLAT BAR TRACK, ON AFT SIDE OF MAST. LENGTH OF TRACK 4' 0" (30)

DRG. No 32/1/09/0

CONTESSA 32

STANDING & RUNNING RIGGING SCHEDULE

J.C. ROGERS, G.R.P. BOATBUILDERS,
WATERLOO RD, LYMINGTON, HANTS.

Drawn by 26/3/76

32 No 9